



		DIFFUSER POSITION			
		1	2	3	4
FLOW L/MIN	15	13	6		
	30		15	7	
	45			12	7
	60			16	10
		SPINNING SPEED		RPM	

TECHNICAL DATA	
temperature max	90°C
pressure max	500 bar
flow	15-60 l/min
washing cicle time	4.8 min
min. pass-through hole dia.	140 mm (manual)
water inlet	1/2" G
inlet filter	700 micron
material	INOX
seals	NBR
nozzle size	1/4" NPT
nozzles positions	2 - 4
weight	9.5 Kg

總代理
思沛雅噴霧器材有限公司
 22205 新北市深坑區北深路三段270巷8號3樓 TEL. 02-8662-6968 FAX. 02-8662-6967
 Website : www.sprayernozzle.com.tw E-mail : sales@sprayernozzle.com.tw

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5	 CLEANING HEADS MONTECCHIO E. (RE) - ITALY
FOGLIO	XXXX						
DATA	XX.XX.XX						
GREZZO	TOLLERANZE GENERALI classe m UNI-EN 22768/1						DEIGN.: CR CONTR.: DM DATA: 16.11.06 MOD. SCALE: 1:1 A4 0
~ = ✓	0+6	6+30	30+120	120+400	400+1000	1000+2000	
± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2		
SGROSS. ∇ = 3.2/∇	NOTE:						CODICE: MW 586AA.02
FINITURA ∇∇ = 1.6/∇	MATERIALE:						
RETTIFICA ∇∇∇ = 0.8/∇	DESCRIZIONE: MW 586AA.02 INSTALLATION DRAWING						