


TECHNICAL DATA	
O.RING	EPDM
SLIPPER	PTFE+CARBON FIBER
INLET FILTER	700 MICRON
NOZZLES POSITIONS	2 - 4
NOZZLES CIRCLE	ON REQUEST
NOZZLES THREAD	1/4"NPT
MAX OPERATING FLOW	60 L/MIN
MAX OPERATING PRESSURE	200 bar
MAX TEMPERATURE	90 °C
MATERIAL	INOX AISI 316
DIFFUSER POSITION	SEE CHART
ROTATION SPEED	SEE CHART
WEIGHT	7.1 KG

		DIFFUSER POSITION			
		1	2	3	4
FLOW L/MIN	15	13	6		
	30		15	7	
	45			12	7
	60			16	10
		SPINNING SPEED		RPM	

ON REQUEST

**SPRAYER** 總代理 思沛雅噴霧器材有限公司

22205 新北市深坑區北深路三段270巷8號3樓 TEL. 02-8662-6968 FAX. 02-8662-6967  
 Website : www.sprayernozzle.com.tw E-mail : sales@sprayernozzle.com.tw

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5	 CLEANING HEADS MONTECCHIO E. (RE) - ITALY
	FOGLIO	XXXX					
GREZZO	DATA	XX.XX.XX					
~ = ✓	TOLLERANZE GENERALI classe m UNI-EN 22768/1						
	±0.6	6±30	30±120	120±400	400±1000	1000±2000	
SGROSS.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	
▽ = 3.2/▽	NOTE: VERSION 05						
FINITURA	MATERIALE: INOX						
▽▽ = 1.6/▽	DESCRIZIONE: PW 060 SL						
RETTIFICA	APPLICATION DRAWING						
▽▽▽ = 0.8/▽	CODICE: PW 060 SL						
DISEGN.: CR CONTR.: DM DATA: 21.11.08 MOD. SCALA 1:1 A3 0							