


TECHNICAL DATA	
O.RING	EPDM
SLIPPER	PTFE+CARBON FIBER
INLET FILTER	700 MICRON
NOZZLES POSITIONS	2 - 4
NOZZLES CIRCLE	ON REQUEST
NOZZLES THREAD	1/4"NPT
MAX OPERATING FLOW	60 L/MIN
MAX OPERATING PRESSURE	200 bar
MAX TEMPERATURE	90 °C
MATERIAL	INOX AISI 316
DIFFUSER POSITION	SEE CHART
ROTATION SPEED	SEE CHART
WEIGHT	7.1 KG

		DIFFUSER POSITION			
		1	2	3	4
FLOW L/MIN	15	78	36		
	30		90	42	
	45			72	42
	60			96	60
		SPINNING SPEED		RPM	

ON REQUEST

**SPRAYER** 總代理 思沛雅噴霧器材有限公司

22205 新北市深坑區北深路三段270巷8號3樓 TEL. 02-8662-6968 FAX. 02-8662-6967  
 Website : www.sprayernozzle.com.tw E-mail : sales@sprayernozzle.com.tw

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5	 CLEANING HEADS MONTECCHIO E. (RE) - ITALY
FOGLIO	XXXX						
DATA	XX.XX.XX						
GREZZO	TOLLERANZE GENERALI classe m UNI-EN 22768/1						DISEGN.: CR   CONTR.: DM DATA: 21.11.08   MOD.
~ = ✓	0±6	6±30	30±120	120±400	400±1000	1000±2000	
SGROSS.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	SCALA 1:1   A3   0
▽ = 3.2/▽	NOTE: VERSION 05						
FINITURA	MATERIALE: INOX						CODICE: PW 060 SP
▽▽ = 1.6/▽	DESCRIZIONE: PW 060 SP APPLICATION DRAWING						
RETTIFICA							
▽▽▽ = 0.8/▽							