



TECHNICAL DATA	
O.RING	NBR - EPDM - VITON
SLIPPER	PTFE+CARBON FIBRE
BUSHING	AISI 316
FILTER	700 MICRON
NOZZLES POSITIONS	4
NOZZLES THREAD	1/4" G
OPERATING FLOW RANGE	15 - 60 L/min
OPERATING PRESSURE RANGE	5 - 200 bar
MAX OPERATING TEMPERATURE	90 °C
MATERIAL	INOX AISI 316
ORBITAL GEARS	FIXED Z=128 ROTATING Z=16
MODULE	2
DIFFUSER SPEED SETTING POSITIONS	4
ROTATION SPEED	SEE CHART
FULL CYCLE	1 ROTATION
FULL CYCLE TIME	5 seconds AT 12 RPM
WEIGHT	9.6 KG

		POSIZIONE DIFFUSORE DIFFUSER POSITION			
		1	2	3	4
PORTATA FLOW L/MIN	15	13	6		
	30		15	7	
	45			12	7
	60			16	10

VELOCITA' ROTAZIONE GIRI/MIN
SPINNING SPEED RPM

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5
FOGLIO DATA	XXXX XX.XX.XX					
GREZZO	TOLLERANZE GENERALI classe m UNI-EN 22768/1					
~ = ✓	0+6	6+30	30+120	120+400	400+1000	1000+2000
SGROSS.	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2
▽ = 3.2/						
FINITURA	MATERIALE:					
▽ = 1.6/						
RETTIFICA	DESCRIZIONE: INSTALLATION DRAWING PW086A					
▽ = 0.8/						

CLEANING HEADS
MONTECCHIO E. (RE) - ITALY

DISIGN.: CR | CONTR.: DM
DATA: 09.07.14 | MOD.

SCALA: 1:2 | A3 | 0

CODICE: PW086A