

UGELLI/NOZZLE STANDARD

	Giallo Yellow Ø0.9	Rosso Red Ø1	Blue Blue Ø1.15	Verde Green Ø1.3	Nero Black Ø1.5
8	120	70	40	30	15
12		150	100	60	40
15			150	90	60
18				140	80

PRESSIONE/PRESSURE (bar)




思沛雅噴霧器材有限公司

22205 新北市深坑區北深路三段270巷8號3樓 TEL. 02-8662-6968 FAX. 02-8662-6967
Website : www.sprayernozzle.com.tw E-mail : sales@sprayernozzle.com.tw

DATI TECNICI	
temperatura max	90°C
pressione max	150 bar
portata max	18 l/min
motore elettrico	12v c.c.
alimentazione	220/240v 50Hz
diametro minimo foro	42 mm
tenute	nbr
ugelli	2
materiale	Inox AISI 316
massa	3.100 Kg

TECHNICAL DATA	
temperature max	90°C
pressure max	150 bar
flow max	18 l/min
electric motor	12v c.c.
power supply	220/240v 50Hz
min. pass-through hole dia.	42 mm
tenute	nbr
nozzle size	2
material	inox AISI 316
weight	3.100 Kg

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5
FOGLIO	XXXX					
DATA	XX.XX.XX					
GREZZO	TOLLERANZE GENERALI classe m UNI-EN 22768/1					
	0÷6	6÷30	30÷120	120÷400	400÷1000	1000÷2000
SGROSS.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2
▽ = 3.2/▽	NOTE:					
FINITURA	MATERIALE:					
▽▽ = 1.6/▽	DESCRIZIONE: DIMENSION DRAWING					
RETTIFICA	DESCRIZIONE: DIMENSION DRAWING					
▽▽▽ = 0.8/▽						



CLEANING HEADS
MONTECCHIO E. (RE) - ITALY

DISIGN.: CR | CONTR.: DM
DATA: 20.01.2005 | MOD.
SCALA: 1:3 | A4 | 0

CODICE: Roty'018