



2 1/8" NPT NOZZLES POSITIONS ON 64° CONE
 2 1/8" NPT NOZZLES POSITIONS ON 96° CONE

PLUG NOZZLES POSITIONS NOT USED

SPRAYER 總代理 思沛雅噴霧器材有限公司
 22205 新北市深坑區北深路三段270巷8號3樓 TEL. 02-8662-6968 FAX. 02-8662-6967
 Website : www.sprayernozzle.com.tw E-mail : sales@sprayernozzle.com.tw

file: SW 048 SL cm

TECHNICAL DATA	
temperature max	90°C
pressure max	150 bar
flow	15-60 l/min
spinning speed	25 rpm
water inlet	1/2" G
filter	700 micron
nozzle thread	1/8" NPT
nozzles positions	2 on 64° cone - 2 on 96° cone
weight	3.0 Kg

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5
	FOGLIO	XXXX				
GREZZO	DATA	XX.XX.XX				
~ = ✓	TOLLERANZE GENERALI classe m UNI-EN 22768/1					
SGROSS.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2
▽ = 3.2/▽	NOTE:					
FINITURA	MATERIALE: INOX					
▽▽ = 1.6/▽	DESCRIZIONE: ORBITAL SURFACE WASHING					
RETTIFICA	INSTALLATION DRAWING					
▽▽▽ = 0.8/▽						

Bolondi
 CLEANING HEADS
 MONTECCHIO E. (RE) - ITALY

DISEGN.: CR | CONTR.: DM
 DATA: 17.02.09 | MOD.
 SCALA: 1:1 | A4 | 0

CODICE:
 SW 048 SL