


總代理

思沛雅噴霧器材有限公司

22205 新北市深坑區北深路三段270巷8號3樓 TEL. 02-8662-6968 FAX. 02-8662-6967
 Website : www.sprayernozzle.com.tw E-mail : sales@sprayernozzle.com.tw

DATI TECNICI (I)	
temperatura max	90°C
pressione max	200 bar
portata max	30-120 l/min
velocità di rotazione	120 g/min
tempo ciclo breve	15"
tempo ciclo completo	30"
diametro minimo foro entrata	160 mm
ugelli	1/2"G
massa	1/4"G
	7.5 Kg

TECHNICAL DATA (GB)	
temperature max	90°C
pressure max	200 bar
flow max	30-120 l/min
spinning speed	120 g/min
short washing cycle time	15"
complete washing cycle time	30"
min. pass-through hole dia.	160 mm
water inlet	1/2"G-BSP-M
nozzle size	1/4"G-BSP-M
weight	7.5 Kg

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5
FOGLIO	XXXX					
DATA	XX.XX.XX					
GREZZO	TOLLERANZE GENERALI classe m UNI-EN 22768/1					
~ = ✓	0+6	6+30	30+120	120+400	400+1000	1000+2000
SGROSS.	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2
▽ = 3.2/	NOTE: VERSIONE 06					
FINITURA	MATERIALE:					
▽ = 1.6/						
RETTIFICA	DESCRIZIONE: AQUAMOTOR SECTOR PER LAVACASSONETTI 120°					
▽ = 0.8/						
 CLEANING HEADS MONTECCHIO E. (RE) - ITALY						
DISEGN.: CR CONTR.: DM						
DATA: 02.08.01						
SCALA		1:1 A4 0				
CODICE:		SW 120CF				