


TECHNICAL DATA	
temperature max	90°C
pressure max	150 bar
flow	15-60 l/min
spinning speed	80 rpm
washing cycle time	45 sec.
min. pass-through hole dia.	120 mm
water inlet	1/2" G
inlet filter	700 micron
nozzle size	1/8" NPT
nozzles positions	2 - 4
weight	3.2 Kg

SPRAYER 總代理
思沛雅噴霧器材有限公司
 22205 新北市深坑區北深路三段270巷8號3樓 TEL. 02-8662-6968 FAX. 02-8662-6967
 Website : www.sprayernozzle.com.tw E-mail : sales@sprayernozzle.com.tw

file: SW 186 WKC cm1

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5	 CLEANING HEADS MONTECCHIO E. (RE) - ITALY
FOGLIO	XXXX						
GREZZO	DATA	XX.XX.XX					
~ = √	TOLLERANZE GENERALI classe m UNI-EN 22768/1						CODICE: SW 186 WKC
SGROSS.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	
▽ = 3.2/	NOTE: ex RW186 WKC 16.02.09						DESCRIZIONE: SW 186 WKC INSTALLATION DRAWING
FINITURA	MATERIALE: INOX						
▽ = 1.6/							
RETTIFICA							
▽ = 0.8/							