



TECHNICAL DATA

O.RING	EPDM
SLIPPER	PTFE+CARBON FIBRE
FILTER	NONE
NOZZLES POSITIONS	2 OR 4
NOZZLES TYPE	SPECIAL NOZZLE XB 030
MAX OPERATING FLOW	30 L/min – 8 USG/min
MAX OPERATING PRESSURE	150 bar – 2100 psi
MAX OPERATING TEMPERATURE	90 °C – 194°F
MATERIAL	INOX AISI 316
LUBRICANTS	NONE
CONICAL GEARS	FIXED Z=23 ROTATING Z=25
MODULE	1
COMPLETE CYCLE	25 ROTATIONS
COMPLETE CYCLE TIME	1.1 MIN.
ROTATION SPEED	24 RPM
WEIGHT	4.6 KG – 10 LBS

SPRAYER 總代理 思沛雅噴霧器材有限公司
 22205 新北市深坑區北深路三段270巷8號3樓 TEL. 02-8662-6968 FAX. 02-8662-6967
 Website : www.sprayernozzle.com.tw E-mail : sales@sprayernozzle.com.tw

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5
FOGLIO	XXXX					
DATA	XX.XX.XX					
GREZZO	TOLLERANZE GENERALI classe m UNI-EN 22768/1					
~ = ✓	0÷6	6÷30	30÷120	120÷400	400÷1000	1000÷2000
SGROSS. ∇ = 3.2/∇	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2
FINITURA ∇∇ = 1.6/∇	NOTE:					
RETTIFICA ∇∇∇ = 0.8/∇	DESCRIZIONE: APPLICATION DRAWING XB 031AAE_BQ.01					

Bolondi
 CLEANING HEADS
 MONTECCHIO E. (RE) – ITALY

DISEGN.: CR CONTR.: DM
 DATA: 27.08.08 MOD.
 SCALA 1:2 A4 0
 CODICE: XB 031AAE_BQ.01