



TECHNICAL DATA	
O.RING	NBR - EPDM - VITON
SLIPPER	PTFE+CARBON FIBRE
FILTER	700 MICRON
NOZZLES POSITIONS	2 - 4
NOZZLES TYPE	SPECIAL XB 030
MAX OPERATING FLOW	30 L/min
MAX OPERATING PRESSURE	200 bar
MAX OPERATING TEMPERATURE	90 °C
MATERIAL	INOX AISI 304
CONICAL GEARS	FIXED Z=23 ROTATING Z=25
MODULE	1
COMPLETE CYCLE	25 ROTATIONS
COMPLETE CYCLE TIME	1.1 MIN.
ROTATION SPEED	24 RPM
WEIGHT	7.5 KG

RUGOSITA' (UNI 4800)	MODIFICA	1	2	3	4	5	Bolondi CLEANING HEADS MONTECCHIO E. (RE) - ITALY	
FOGLIO	DATA	xxxx						
GREZZO	TOLLERANZE GENERALI	classe m UNI-EN 22768/1					DATA: 18.05.09	DESEGN.: CR CONTR.: DM
~ = √	0±6	6±30	30±120	120±400	400±1000	1000±2000	MOD.	
SGROSS.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	SCALE	
∇ = 3.2/∇	NOTE:						1:3	
FINITURA	DESCRIZIONE: APPLICATION DRAWING						A4	
∇∇ = 1.6/∇	XB 031 AAH						0	
RETTIFICA							CODICE:	
∇∇∇ = 0.8/∇							XB 031 AAH	