


總代理

思沛雅噴霧器材有限公司

22205 新北市深坑區北深路三段270巷8號3樓 TEL. 02-8662-6968 FAX. 02-8662-6967  
 Website : www.sprayernozzle.com.tw E-mail : sales@sprayernozzle.com.tw

TECHNICAL DATA

temperature max	90°C
pressure max	500 bar
flow	15-60 l/min
spinning speed	16 rpm
washing cycle time	6 min
min. pass-through hole dia.	120 mm
water inlet	1/2" G
inlet filter	700 micron
material	INOX
seals	NBR
nozzle size	1/4" NPT
nozzles positions	2 - 4
weight	10.5 Kg

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5	 CLEANING HEADS MONTECCHIO E. (RE) - ITALY
	FOGLIO	XXXX					
GREZZO ~ = ✓	DATA	XX.XX.XX					DISEGN.: CR   CONTR.: DM DATA: 13.05.08   MOD.
	TOLLERANZE GENERALI classe m UNI-EN 22768/1						
SGROSS. ▽ = 3.2/	0 ÷ 6	6 ÷ 30	30 ÷ 120	120 ÷ 400	400 ÷ 1000	1000 ÷ 2000	SCALA 1:1   A4   0
	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2	
FINITURA ▽ = 1.6/	NOTE:						CODICE: XB 586A
RETTIFICA ▽ = 0.8/	DESCRIZIONE: XB 586A INSTALLATION DRAWING						