


總代理

思沛雅噴霧器材有限公司

22205 新北市深坑區北深路二段270巷8號3樓 TEL. 02-8662-6968 FAX. 02-8662-6967  
 Website : www.sprayernozzle.com.tw E-mail : sales@sprayernozzle.com.tw

DATI TECNICI	
temperatura max	60°C
pressione max	120 bar
portata max	15-25 l/min
motore elettrico	12v c.c.
alimentazione	220/240v 50Hz
diametro minimo foro	42 mm
tenute	nbr
ugelli	2
materiale	Inox AISI 316
massa	3.100 Kg

TECHNICAL DATA	
temperature max	60°C
pressure max	120 bar
flow max	15-25 l/min
electric motor	12v c.c.
power supply	220/240v 50Hz
min. pass-through hole dia.	42 mm
tenute	nbr
nozzle size	2
material	inox AISI 316
weight	3.100 Kg

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5	 CLEANING HEADS MONTECCHIO E. (RE) - ITALY
FOGLIO DATA	XXXX XX.XX.XX						
GREZZO	TOLLERANZE GENERALI classe m UNI-EN 22768/1						DISEGN.: CR   CONTR.: DM DATA: 23.12.02   MOD.
SGROSS.	0÷6	6÷30	30÷120	120÷400	400÷1000	1000÷2000	
FINITURA	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	SCALA
RETTIFICA	NOTE:	MATERIALE:					1:3
		DESCRIZIONE: XC 020 ASPIRATORE					A3
							0
							CODICE:
							XC020-Asp