



TECHNICAL DATA

O.RING	EPDM
SLIPPER	PTFE+CARBON FIBRE
FILTER	700 MICRON
NOZZLES POSITIONS	2-4
NOZZLES TYPE	1/8"NPT
MAX OPERATING FLOW	60 L/min
MAX OPERATING PRESSURE	150 bar
MAX OPERATING TEMPERATURE	90 °C
MATERIAL	INOX AISI 316
CONICAL GEARS	FIXED Z=29 ROTATING Z=31
MODULE	1
COMPLETE CYCLE	31 ROTATIONS
COMPLETE CYCLE TIME	30 SEC
ROTATION SPEED	60 RPM
WEIGHT	7.5 KG

**SPRAYER** 總代理  
**思沛雅噴霧器材有限公司**  
 22205 新北市深坑區北深路三段270巷8號3樓 TEL. 02-8662-6968 FAX. 02-8662-6967  
 Website : www.sprayernozzle.com.tw E-mail : sales@sprayernozzle.com.tw

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5
	FOGLIO	XXXX				
GREZZO ~ = ✓	DATA	XX.XX.XX				
	TOLLERANZE GENERALI classe m UNI-EN 22768/1					
SGROSS. ▽ = 3.2/✓	0÷6	6÷30	30÷120	120÷400	400÷1000	1000÷2000
	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2
FINITURA ▽▽ = 1.6/✓	NOTE: file: XC 061 AAH cm					
	DESCRIZIONE: APPLICATION DRAWING XC031_180°FR-AAM.01					
RETTIFICA ▽▽▽ = 0.8/✓						

**Bolondi**  
 CLEANING HEADS  
 MONTECCHIO E. (RE) - ITALY  
 DISEGN.: GR | CONTR.: DM  
 DATA: 07.05.08 | MOD.  
 SCALA  
 1:2 | A4 | 0  
 CODICE:  
 XC031\_180°FR-AAM.01