


TECHNICAL DATA	
O.RING	EPDM
SLIPPER	PTFE+CARBON FIBER
BUSHING	NICKEL BRONZE 25%
FILTER	700 MICRON
NOZZLES POSITIONS	4
NOZZLES SIZE	1/8"NPT
OPERATING FLOW	60 L/min
OPERATING PRESSURE	150 bar
MAX TEMPERATURE	90 °C
MATERIAL	INOX AISI 316
GEARS	FIXED Z=29 ROTATING Z=31
MODULE	1
FULL CYCLE	31 ROTATIONS
FULL CYCLE TIME	1.00 MIN. AT 3 BAR AIR PRESSURE
AIR MOTOR	ATLAS COPCO BA 720 INOX
AIR EXHAUST	FESTO SILENCER BP 415 ON MOTOR
WEIGHT	6.5 KG


總代理
思沛雅噴霧器材有限公司
 22205 新北市深坑區北深路三段270巷8號3樓 TEL.02-8662-6968
 Website : www.sprayer.com.tw E-mail : sales@sprayer.com.tw

AIR PRESSURE AND CONSUMPTION			
ROTATION SPEED	29 RPM	1 bar	264 L/min. AIR
ROTATION SPEED	42 RPM	2 bar	288 L/min. AIR
ROTATION SPEED	51 RPM	3 bar	300 L/min. AIR
ROTATION SPEED	58 RPM	4 bar	306 L/min. AIR
ROTATION SPEED	62 RPM	5 bar	312 L/min. AIR
ROTATION SPEED	66 RPM	6 bar	324 L/min. AIR

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5	 CLEANING HEADS MONTECCHIO E. (RE) - ITALY	
	FOGLIO	XXXX						
GREZZO	DATA	XX.XX.XX					DISEGN.: CR CONTR.: DM DATA: 26.05.08 MOD. CODICE: XC 061PDBD S3A	
	TOLLERANZE GENERALI	classe m UNI-EN 22768/1						
SGROSS.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	1:9 A4 0	
FINITURA	DESCRIZIONE:	APPLICATION DRAWING XC 061 PDBD S3A					file: XC 061 PDBD S3A cm	
RETTIFICA								