



DEFLECTED SPRAY


RO系列空心圓錐形噴嘴，針對消防用途所設計，不但能夠產生最佳的消防噴霧效果及大範圍的覆蓋面積，更具有優異的防堵塞性，全系列產品皆通過歐洲消防法規認證。



- 螺牙規格：BSPT、NPT
- 典型應用：消防水噴灑
消防泡沫噴灑
桶槽清洗
廢氣洗滌



噴霧斷面



流量分布：凹形分布



空心圓錐形

噴霧角度 ◁	噴嘴型號			螺牙規格 RG (inch)	噴口直徑 (mm)	不同操作壓力(bar)時的噴霧流量(L/min)					WS (mm)	H (mm)	
	噴嘴形式	流量代碼	材質代碼			1.0	3.0	5.0	6.0	7.0			10.0
130°	ROY 1810 xx yy			1/2"	3.00	4.80	8.10	10.3	11.3	12.2	14.5	25	65
	ROY 2115 xx yy				3.50	6.70	11.5	14.9	16.4	17.6	20.5		
	ROY 2156 xx yy				4.00	9.00	15.6	20.0	22.0	24.0	29.0		
	ROY 2198 xx yy				4.50	11.5	19.8	25.0	28.0	30.0	36.0		
	ROY 2270 xx yy				5.00	15.8	27.0	35.0	39.0	42.0	50.0		
	ROY 2300 xx yy				5.50	18.0	30.0	40.0	44.0	48.0	57.0		
	ROY 2390 xx yy				6.00	23.0	39.0	50.0	55.0	60.0	71.0		
	ROY 2470 xx yy				6.50	27.0	47.0	61.0	66.0	72.0	86.0		
	ROY 2550 xx yy				7.00	31.0	55.0	72.0	77.0	84.0	91.0		
	ROY 2700 xx yy				8.00	41.0	70.0	92.0	103	112	130		
	ROY 2910 xx yy				9.00	52.0	91.0	117	129	140	165		
ROY 3110 xx yy				10.0	64.0	110	139	152	165	200			
ROY 3164 xx yy				12.0	95.0	164	214	236	255	290			
130°	ROY 1811 xx yy			3/4"	3.00	4.80	8.10	10.3	11.3	12.2	14.5	27	65
	ROY 2116 xx yy				3.50	6.70	11.5	14.9	16.4	17.6	20.5		
	ROY 2157 xx yy				4.00	9.00	15.6	20.0	22.0	24.0	29.0		
	ROY 2199 xx yy				4.50	11.5	19.8	25.0	28.0	30.0	36.0		
	ROY 2271 xx yy				5.00	15.8	27.0	35.0	39.0	42.0	50.0		
	ROY 2301 xx yy				5.50	18.0	30.0	40.0	44.0	48.0	57.0		
	ROY 2391 xx yy				6.00	23.0	39.0	50.0	55.0	60.0	71.0		
	ROY 2471 xx yy				6.50	27.0	47.0	61.0	66.0	72.0	86.0		
	ROY 2551 xx yy				7.00	31.0	55.0	72.0	77.0	84.0	91.0		
	ROY 2701 xx yy				8.00	41.0	70.0	92.0	103	112	130		
	ROY 2911 xx yy				9.00	52.0	91.0	117	129	140	165		
	ROY 3111 xx yy				10.0	64.0	110	139	152	165	200		
	ROY 3165 xx yy				12.0	95.0	164	214	236	255	290		



規格代碼

規格代碼	螺牙形式	過濾器材質	
		紅銅	不銹鋼
FB	BSP/BSPT	•	
FN	NPT	•	
GB	BSP/BSPT		•
GN	NPT		•
SN	NPT	不含過濾器	

洽詢方式說明

範例：ROY 1810 B3 FB

